

# INSTANTANEOUS SAFETY GEAR TYPE RF

AUTHORISED DISTRIBUTOR FOR UK

WE CATCH YOU



**SASSI LIFT SYSTEMS**

5 Blackwell Drive,  
Springwood Industrial Estate,  
Braintree, Essex CM7 20J  
United Kingdom  
Tel: 01376 550666  
Fax: 01376 341219  
sales@sls-ltd.co.uk  
<http://www.sls-ltd.co.uk>



## APPLICATION FIELD

	RF0001	RF0002
<b>Tripping speed [m/s]</b>	<b>Max. total mass [kg]</b>	<b>Max. total mass [kg]</b>
0.5	8,890	3,260
0.6	8,550	3,140
0.7	8,180	3,000
0.8	7,800	2,860
0.9	7,400	2,720
1.0	7,010	2,570
1.1	6,620	2,430
1.2	6,230	2,290
1.32	5,800	2,130
1.65	4,720	1,730
Max. rated speed car	0.63 m/s	0.63 m/s
Max. rated speed counterweight	1.00 m/s	1.00 m/s
Max. tripping speed car	1.00 m/s	1.00 m/s
Max. tripping speed counterweight	1.65 m/s	1.65 m/s
Running surface width	28 mm	28 mm
Blade width	16 mm	9 -10 mm

## FEATURES

- › Compact size  
Dimension RF0001: 134 x 120 x 50  
Dimension RF0002: 106 x 120 x 50
- › Tripping is effected by the overspeed governor or a slack rope
- › Suited for mounting at the counterweight (particularly RF0002)



**Sautter Lift Components**

Please find further information in our product brochure 'Safety gears by SLC'

Subject to technical modifications