

OLEO OIL BUFFERS

YOUR AFFORDABLE, REDUCED PIT HEIGHT BUFFER SOLUTION



1.0 - 1.8 M/S MAX
RATED SPEED



380-3250KG
LOAD RANGE



COMPACT &
LIGHTWEIGHT



PRECHARGED
WITH OIL



QUICK & EASY
INSTALLATION



COMMON
APPLICATION



LSB 10

LSB 16

LSB 18

MODEL	LSB 10*	LSB 16	LSB 18
Rated Speed - m/s	1.00	1.60	1.80
Maximum Speed (115%) - m/s	1.15	1.84	2.07
Stroke (min) - mm	73.4	173.5	219.5
Impact Mass Range - kg	380-3250	450-3250	450-3250
Height (fully extended/max) - mm	222.2	485.5	577.5
Height (compressed/min) - mm	145.9	306.9	352.9
Weight (dry) - kg	3.6	6.6	7.4
Oil Volume - litres	0.5	0.8	1.0
Reduced Stroke (ASME A17.1) - m/s	1.47	2.27	2.55

Alternative OLEO Buffers for 1.6m/s – 1.8m/s at increased maximum load:

SEB16.2

Hydraulic /Oil Buffer



1.6 M/S MAX
RATED SPEED



450-4545KG
LOAD RANGE



£253

SEB 18.2

Hydraulic /Oil Buffer



1.8 M/S MAX
RATED SPEED



450-4545KG
LOAD RANGE



£265

All prices subject to stock availability + VAT & Delivery to be added.